## DOUG FLEENOR DESIGNE

### **Rerun Portable**

model: RERUN-P technical data sheet

The *Rerun Portable* is a lighting control station capable of storing up to ten 40-minute shows. Shows are recorded by capturing the output of a DMX512 console. The recorded show start and end points may be trimmed non-destructively. Each show can be set to hold the last look, loop to itself or link to another show. Shows are started by pressing one of the ten show buttons.

The Rerun Portable is housed within a rugged Pelican<sup>™</sup> water resistant case. Just under the clear case lid are the DMX512 input and keypad. The DMX512 out and attached wall wart power supply connections pass through the case on liquid tight strain reliefs.

The *Rerun Portable* system can work in conjunction with a lighting console, automatically switching between recorded shows and console control. When the console generates DMX512 the *Rerun Portable* retransmits the incoming DMX512 data. Thus the console operates normally. Upon loss of DMX512 from the console, the *Rerun Portable* starts its previous show.

Rerun also comes in an architectural version (model RERUN-A) and a rack mount version (model RERUN-RM)

#### **SPECIFICATIONS:**

Connector: DMX512 Input: DMX512 Output:

Gold plated 5 pin Neutrik

Gold plated 5 pin Neutrik

on 18" pigtail

Connector pin out: DMX512 Input DMX512 Output

Input circuit: ESD protected EIA-485 transceiver (LT1785)

Output circuit: ESD protected EIA-485 transceiver (LT1785)

Isolation: None: DMX input is not isolated from DMX output

Indicators: Ten green SHOW LEDs

One green PAUSE LED One green LOOP LED One yellow START LED One yellow END LED

One red INPUT/RECORD LED

User controls: Ten [SHOW] buttons

One [PAUSE] button
One [LOOP] button
One [REWIND] button
One [FORWARD] button

One recessed [RECORD] button



# DOUG FLEENOR DESIGNE

**SPECIFICATIONS:** (Continued)

Option Jumpers:		INSTALLED	REMOVED
	JP1	Recording enabled	Recording/editing disabled
	JP2	Run show on DMX512 loss	Hold last look on DMX512 loss
	JP3	Normal operation	Run hardware test
	JP4	Normal operation	Disable operation
	JP5	Unused	Unused
	JP6	Normal operation	Erase memory (DANGER!)

Power input: Attached universal power supply 100 - 240VAC, 50/60 hertz, 5 watts

Color: Case: Clear with yellow liner

Keyboard: Black anodized with white silk screened nomenclature

Size: 5.06"H × 3.12"D × 7.50"W

#### **Limited Manufacturer's Warranty**

Products manufactured by Doug Fleenor Design (DFD) carry a five-year parts and labor warranty against manufacturing defects. It is the customer's responsibility to return the product to DFD at the customer's expense. If covered under warranty, DFD will repair the unit and pay for return ground shipping. If a trip is necessary to the customer's site to solve a problem, the expenses of the trip must be paid by the customer.

This warranty covers manufacturing defects. It does not cover damage due to abuse, misuse, negligence, accident, alteration, or repair by other than by Doug Fleenor Design.

Most non-warranty repairs are made for a fixed \$50.00 fee, plus shipping.

### Doug Fleenor Design, Inc.

396 Corbett Canyon Road Arroyo Grande, CA 93420 (805) 481-9599 voice and FAX (888) 4-DMX512 toll free (888) 436-9512

web site: http://www.dfd.com e-mail: info@dfd.com

